HOSPITAL TRACK SYSTEM



HOSPITAL TRACK SYSTEM



Product Information

- Sleek and functional Hospital Track System
- Simple and quick installation; low maintenance
- Bendable: inside and outside bends with an 8" (20cm) radius or a continuous curve
- Colour: white
- Lengths: up to 19ft (5.8mtr)
- Track quality: aluminum, chromated, powder coated and anti-friction treated
- Glide quality: polyacetal (POM), UV-protected
- Can also be used with Ripplefold carriers

For use in

Healthcare sector and sanitary rooms, changing rooms, dental / medical offices, or anywhere a high quality, contemporary and efficient suspension system is required.

Limited Life-time Warranty.

Aluminum extrusion 6063 T5

Weight: 500 gr/mtr (5.36 oz/ft)

Profile

19.6mm (25/32") 30mm (1-3/16")

	HTS Track 19ft (5.8mtr) / length Aluminum extrusion, powder coated, lubricated.	HT1900.25 5 lengths/case	S	HTS Flexible Dust Strip	HT2100.25
J S	HTS Carrier with Metal Hook UV-protected	HT2210.25 500/box	888	HTS Track Connector Use with T-Endcap for T-connection	HT2400.25 100/box
Ð	HTS Endstop Metal, to secure endcap	HT2300.25 100/box		HTS Track-bridge Long	HT2440.25 10/box
J	HTS Endcap	HT2320.25 20/box	T and a second s	HTS Track-bridge Short	HT2420.25 10/box
1	HTS T-Endcap Use for T-connection	HT2340.25 20/box	Ø	HTS Wall Bracket	HT3100.25 20/box
<u>) </u>	HTS Suspension Ceiling Bracket Standard Length = 39" (1mtr) Custom sizes available up to 16	HT3050.25 1/each 5'4" (5mtr)	Ø	Smart Klick Ceiling Bracket	KS3010.25 100/box
-	Standard Ripplefold Carriers Ap	pplicable 1000/roll	Bending	Min. 22" (55cm)	Min. R=20" (50cm)

www.textiletrimmings.com